


Suzuki TM-125K Challenger

\$ 650
C&H



Primary kick starter

Aluminum front forks

21" front wheel



High tuned competition muffler with silencer

Single leading shoe front brake

CCI automatic lube

Aluminum alloy rims

Length	79.1"
Width	36.8"
Height	43.1"
Wheel Base	52.6"
Ground Clearance	7.9"
Dry Weight	189 lbs.
Engine Type	2-stroke, air-cooled aluminum, single cylinder
Bore & Stroke	2.20" x 1.97"
C.C.	123
Compression Ratio	7.5 : 1
Carburetor	VM26SC
Maximum Output	18 hp/10000 rpm
Maximum Torque	10.0 ft.-lbs./ 8000 rpm
Ignition System	PEI (Pointless Electronic Ignition)
Transmission	5-speed, constant mesh
Clutch	Multi-plate, wet disc
Starter	Primary kick
Brakes: Front	Right hand, internal expanding, single leading
Rear	Right foot, internal expanding
Suspension: Front	Telescopic, oil-dampened
Rear	Swinging arm, oil-dampened
Front Fork Travel	5.7"
Tires: Front	3.00-21 4PR, Full Knobby
Rear	3.50-18 4PR, Full Knobby
Color	Aspen Yellow
Fuel Tank Capacity	1.3 gals.
Oil Tank Capacity	1.2 pts.

All prices and specifications subject to change without notice.



The TM-125K model is
expressly excluded from
any Suzuki warranty.

Suzuki: built to take on the country.